solidian•kelteks

reinforcing the future

Kelteks d.o.o. Or. Slavka Rozgaja 3 47000 Karlovac, Croatia - EU sales@solidian-kelteks.com
www.solidian-kelteks.com
P +385 47 693 314

build solid.



	TIFIED	(17)
ISC	9001	
	0 14001	TOT TRAD

ROLL DIMENSIONS:

Width: 100cm | Length: 50m | Total: 50m²

COUNTRY OF ORIGIN: Croatia

YEAR OF PRODUCTION:

2025

25/017

TECHNICAL INSTRUCTIONS:

Fibreglass mesh for reinforcing floor coverings. It is laid over the entire surface within the freshly applied material that is being reinforced. Store in a dry and protected place. Classification markings are not applicable. Use within 3 years (including the year of production).





DECLARATION OF PERFORMANCE: 25/017

- 1. Unique identification code of the product type: Primafloor 130, glass fibre mesh
- 2. Intended use: Reinforcing floor coverings
- 3. Manufacturer: KELTEKS d.o.o., Dr. Slavka Rozgaja 3, HR-47000 Karlovac
- 4. Production line: Dr. Slavka Rozgaja 3
- 6. System of AVCP: 3
- 7b. Technical regulation on construction products (NN 35/18, 104/19) Appendix II, Item II.1.2.3. Approved body: Institute IGH d.d., Janka Rakuše 1, Zagreb
- Report on Initial Type Testing of glass fibre mesh, No. 61060-179/12 dated 21.06.2012., and its revision 61060-180/12 from 21.06.2012. Report on evaluation of Initial Type Testing of glass fibre mesh, No. 61060-180/12 dated 21.06.2012. (evidence number 1/05).
- 9. Declared performance/s:
 - Mass per unit area: 130 g/m2 ± 10%
 - Mesh size: 36 x 36 mm
 - Combustible matter content: ≥ 15 %
 - Tensile strength (average value): Warp: > 40 N/mm, Weft: > 40 N/mm
 - Tensile strength after ageing in alkaline solution: > 50% of initial tensile strength
- 10. The previously determined property of the product is in accordance with the published properties. This declaration of performance is issued in accordance with the Law on construction products (NN 76/13, 30/14, 130/17, 39/19, 118/20), under the sole responsibility of the previously determined manufacturer.

distributed by:



\oplus